

# Domtar POS 74S - 3.2

## Product Specifications

Caliper	Basis Weight	Brightness (UV Included)	Thermal Response - Nominal				Gurley Stiffness Nominal (mg)		Elmendorf Tear Nominal (g)		Parker Print Surf
			Static - (°C ± 5°)		Dynamic - Atlantek 400 (mJ/mm <sup>2</sup> )		MD:	CD:	MD:	CD:	
			0.2 ODU	87	0.2 ODU	5.9	100	50	50	50	
mils	17 x 22— 500 (lbs)	>85	1.0 ODU	72	1.0 ODU	8.9					
3.20 2.90 - 3.50	18.7 17.6 - 19.8		Max. Density	1.28	Max. Density	1.45					
μm	g/m <sup>2</sup>		Required Temp.	149	Energy Req.	16.0				<2.20	
81.3 73.7 - 88.9	70.3 66.1 - 74.5										

### Features:

- Bond-like feel
- Bright white appearance
- Flexographic printable front and back
- Lithographic printable back side only
- 10 years image life, 3 years storage life (under proper storage conditions for thermal paper)

### Ideal For:

- Point-of-sale
- ATM receipts
- Kiosks
- Parking receipts

### Environmental Characteristics:

- Produced without the use of bisphenol A (BPA)

